



PowerVantage™ 2U Series Twin Tube Compact Fluorescent Lamps

- Operating Voltage: 220V AC/50Hz
- High Lumen Efficiencies:
 - CF8W/2U: > 45 lm/w
 - CF12W/2U: > 50 lm/w
 - CF16W/2U: > 52 lm/w
- Very competitive pricing
- Available Color Temperatures:
 - Warm White: 2700K, 3000K
 - Cool White: 3500K, 4100K
 - Daylight: 5000K, 6500K, 7000K

The PowerVantage™ lamp series are the mainstream product lines featuring industry-standard performances, very competitive pricing, and professional product lineups, most suitable for home lighting and basic commercial lighting applications.

The PowerVantage™ 2U Series lamps are the most popular middle-class CFLs in South-East Asia market, made by Raywa with enhanced reliability and lumen efficiency yet in very competitive pricing.

Other Technical Data


Power Factor:	>0.50
Current Crest Factor:	<1.70
Circuitry Frequency:	>40 KHz
Lamp Base:	E27 Aluminum
Plastic Housing Material:	Non-Inflammable PBT Plastic

Specifications

Generic Model Number	Watts*	Bulb Type	Lamp Base	Additional Information	Rated Initial Lumens*	Rated Avg. Life (hrs)*	CRI*
CF8W/2U/PV/827	8W	2U / T4	E27	Replaces 40W incandescent lamp	285 lm	3,000 hrs	75
CF12W/2U/PV/827	12W	2U / T4	E27	Replaces 60W incandescent lamp	465 lm	3,000 hrs	75
CF16W/2U/PV/827	16W	2U / T4	E27	Replaces 100W incandescent lamp	570 lm	3,000 hrs	75

* Please refer to Footnotes located on last page of this catalogue for definitions of terms, parameters, and symbols. For the most current product information, please go to www.Raywa.com.

Dimensions & Packaging Information



Model Number	A (mm/inch)	B (mm/inch)	C (mm/inch)	Case Quantity	Case Dimensions	Case G.W.
CF8W/2U/PV	140 / 5.51"	44 / 1.73"	26 / 1.02"	50 pcs	42.0x22.0x14.0 (cm)	5.0 Kg
CF12W/2U/PV	160 / 6.30"	44 / 1.73"	26 / 1.02"	50 pcs	42.0x22.0x15.5 (cm)	5.5 Kg
CF16W/2U/PV	170 / 6.69"	44 / 1.73"	26 / 1.02"	50 pcs	42.0x22.0x16.5 (cm)	6.5 Kg