



ProEdge™ Candle Series Self-ballasted Compact Fluorescent Lamps

- Designed in same shapes and with more lumens than traditional incandescent candle bulbs
- 5W Candle CFL has 75 lm more lumens than 25W incandescent candle bulb
- 7W Candle CFL has 30 lm more lumens than 40W incandescent candle bulb
- 9W Candle CFL has 100 lm more lumens than 40W incandescent candle bulb
- Utilize Raywa IBIS Technology for Instant Bright & Instant Starting performance

The ProEdge™ lamp series are Raywa Lighting's professional product lines featuring Industry-leading or Industry-pioneering lamp performances, professionally-schemed product lineups, and attractive pricing, most suitable for professional lighting applications.

The ProEdge™ Candle Series lamps are available in both Candelabra and Medium lamp bases for complete replacements of all types incandescent candle bulbs.

Raywa IBIS Technology



Raywa IBIS (Instant Bright & Instant Starting) is a revolutionary technology breakthrough for the Covered CFLs, with the following advantages and benefits:

- Same or better Run-up Time as a Bare CFL's.
- Ultrashort Stabilization Time at lamp starting.
- Better light contancy at starting.
- Reduces 50% mercury and 100% indium use.
- Reduces 10% of lamp cost.

Specifications

Generic Model Number	Watts*	Bulb Type	Lamp Base	Color Temp.*	Features	Rated Initial Lumens*	Rated Avg. Life*	CRI*
Candelabra E12 Base								
CF5W/C/E12/827	5W	B-10 ¹ / ₂	Cand., E12	2700K	Base-up only IBIS New	225 lm	8,000 hrs	80
CF7W/C/E12/827	7W	B-10 ¹ / ₂	Cand., E12	2700K	Base-up only IBIS New	320 lm	8,000 hrs	80
CF9W/C/E12/827	9W	B-10 ¹ / ₂	Cand., E12	2700K	Base-up only IBIS New	400 lm	8,000 hrs	80
Medium E26 Base Lamps								
CF5W/C/E26/827	5W	B-13	Med., E26	2700K	Base-up only IBIS New	225 lm	8,000 hrs	80
CF7W/C/E26/827	7W	B-13	Med., E26	2700K	Base-up only IBIS New	320 lm	8,000 hrs	80
CF9W/C/E26/827	9W	B-13	Med., E26	2700K	Base-up only IBIS New	400 lm	8,000 hrs	80

* Please refer to Footnote for definitions of terms, parameters, and symbols. For the most current product information, please go to www.Raywa.com.

Dimensions & Packaging Information

Model Number	A	B	C	Case	Case	Case
	(mm/inch)	(mm/inch)	(mm/inch)	Quantity	Dimensions	G.W.
CF5W/C/E12/827	112 / 4.41"	41 / 1.61"	35 / 1.38"	100 pcs	55.5x27x29.5 (cm)	7.5 Kg
CF7W/C/E12/827	112 / 4.41"	41 / 1.61"	35 / 1.38"	100 pcs	55.5x27x29.5 (cm)	7.5 Kg
CF9W/C/E12/827	112 / 4.41"	41 / 1.61"	35 / 1.38"	100 pcs	55.5x27x33.5 (cm)	8.5 Kg
CF5W/C/E26/827	112 / 4.41"	41 / 1.61"	35 / 1.38"	100 pcs	55.5x27x33.5 (cm)	8.5 Kg
CF7W/C/E26/827	112 / 4.41"	41 / 1.61"	35 / 1.38"	100 pcs	55.5x27x41.5 (cm)	10.5 kg
CF9W/C/E26/827	112 / 4.41"	41 / 1.61"	35 / 1.38"	100 pcs	55.5x27x41.5 (cm)	10.5 kg