



## ProEdge™ 3U Series Triple Tube Compact Fluorescent Lamps

- PROCEL approved high performance series
- Lumen Efficiencies:
  - CF15W 3U:  $\geq 55$  lm/w
  - CF21W/24W 3U:  $\geq 60$  lm/w
  - CF26W 3U:  $\geq 62$  lm/w
- Average Lamp Life: 6,000 Hours
- Operating Voltage: 127V AC 60Hz or 220V AC 60Hz
- Available Color Temperatures:
  - Warm White: 2700K, 3000K
  - Cool White: 3500K, 4100K
  - Daylight: 5000K, 6500K, 7000K

The ProEdge™ lamp series are Raywa Lighting's professional product lines featuring Industry-leading or Industry-pioneering lamp performances, professionally-schemed product lineups, and attractive pricing, most suitable for professional lighting applications.

The ProEdge™ 3U Series lamps are the most popular CFLs in South America market, made by Raywa with enhanced reliability and lumen efficiency yet in very competitive pricing.

### Other Technical Data


Wattage Tolerance:	Max.: +5%; Min.: -10%
Power Factor:	>0.50
Lumen Maintenance	$\geq 85\%$ at 2,000 Hours
Lamp Base:	E27 Nickel-plated Copper
Plastic Housing Material:	Non-Inflammable PBT, UV-resistant

### Specifications

Generic Model Number	Watts	Bulb Type	Lamp Base	Additional Information	Approx. Initial Lumens	Rated Avg. Life (hrs)	CRI
CF15W/3U	15W	3U / T4	E27	Replaces 60W incandescent lamp	825 lm	6,000 hrs	>80
CF21W/3U	21W	3U / T4	E27	Replaces 80W incandescent lamp	1,260 lm	6,000 hrs	>80
CF24W/3U	24W	3U / T4	E27	Replaces 90W incandescent lamp	1,440 lm	6,000 hrs	>80
CF26W/3U	26W	3U / T4	E27	Replaces 100W incandescent lamp	1,600 lm	6,000 hrs	>80

\* Lumen data provided here is based on Warm White lamps.

### Dimensions & Packaging Information



Model Number	A (mm/inch)	B (mm/inch)	C (mm/inch)	Case Quantity	Case Dimensions	Case G.W.
CF15W/3U	152 / 5.98"	54 / 2.13"	41 / 1.61"	20 pcs	32.5x23.5x21.5 (cm)	2.7 Kg
CF21W/3U	170 / 6.69"	54 / 2.13"	41 / 1.61"	20 pcs	33.5x23.5x24.0 (cm)	3.0 Kg
CF24W/3U	178 / 7.01"	54 / 2.13"	41 / 1.61"	20 pcs	33.5x23.5x24.0 (cm)	3.5 Kg
CF26W/3U	178 / 7.01"	54 / 2.13"	41 / 1.61"	20 pcs	33.5x23.5x24.0 (cm)	3.5Kg